Special produced webbing to be used in in the poultry farming sector, designed for the collection of eggs in farms.





ECCOLLECTING EXTREMELY LOW • VERY HIGH • CONSTANT

EXTREMELY LOW • ELONGATION

TENACITY

The main characteristics are:

- · 100% High Tenacity (HT) Polypropylene
- · Does not absorb dirt
- Very easy to clean even if when one egg is broken in the conveyor Perfect for a cold washing processes, with pressure hoses
- · Does not absorb liquids. There is no retained humidity
- · Very easy to do the end unions
- · Very good "grip" over the pulling rollers
- · Anti-slip, good product fastening
- Less static electricity than PES and PE (very important in applications where there is friction with other materials)
- High resistance to most chemical agents, resistant to organic solvents, aqueous solutions of acids, bases and salts
- · 100% recyclable
- High resistance to abrasion (longer life for products)
- · Light density: Light product
- · Does not absorb dirt and does not fade

东莞庞莎织造有限公司

广东东莞市沙田镇环保城工业区义沙村 电话:86-769-88689090·传真:86-769-88689091 www.ponsa.com · sales@ponsa.com.cn



WIDTH

INDUSTRIAS PONSA, S.A.

Polígono Industrial "Els Dolors" - C/ Sallent, 64-72 08243 MANRESA (Barcelona) Spain Tel. +34 93 877 35 00 · Fax +34 93 877 08 55 www.ponsa.com · info@ponsa.com



since 1828









